## STROMAG FEED SYSTEM CHECKLIST/SETTINGS

Serial # <u>22-0039</u>	_	Ship Date	
Customer <u>AES</u> (	_		MM/YY
Parts Being Fed BLACK PLAS 1	TIC CLIP	(One Check	klist Per Part)
Controller Brand ROOIX	Model FC	- 200-2	
Input Voltage 110 V 220 V	Feeder Bowl Size <u>\\8</u>	Rotation	cw
Feeder Bowl Tuned To 60 HZ	50 HZ Feeder Bowl Puls	e 60 VPS (Vibrations per	
Feeder Bowl Coil Gap Settings <u>-03</u> IN	<u>∙03</u> IN Coils Paralle	I to Pull Face	/ <u>×</u> N
Controller Settings (Speed) at Shipment:	Bowl <u>So</u> Hoppe	er <u>40</u> I	nline
Main Air Regulator set to <u>40</u> PSI	# of Air Jets on Inline # of Air Jets at Nest # of Air Jets in Bowl 3	Flow Controls	Y N Y N Y <u>X</u> N
Observations Re: Sample Test Parts:  Flash Y X  Mold "Tits" Y  Debris in with Parts Y  Out of Tolerance/Broken Y  Parts Found	N _ X Lubricant, Film, M N _ X Debris Slots in Box	wl '	Y N _ <del>X</del> Y N _ <del>X</del> Y N
		ack Level <u>Keyea</u> ught Y	CE F-N41C
Holdback Cylinder Y N _X_ Comments		Below Deck Y	′ N
Optimal Part Level in Bowl Marked Y_ Comments	N <u>X</u>		
Bowl Level De	elay "ON" <u>2.0</u> Seconds elay "ON" <u>4.0</u> Seconds N N/A	· -	
System Filmed In Operation Y	N Pictures Taken Pr	e-Shipment Y	N
Straps, Blocks, Braces Used in Shipping	Y X N (MUST BE R	EMOVED BEFORE	OPERATION)